

## DIPRO-FOG LUBRICATION/AIR FILTERING UNIT

AND OTHER ACCESSORIES FOR AIR-DRIVEN MACHINES



MFB

The Dipro-fog (MFB) package consists of air filter, regulator, manometer and fog lubrication device, all in one, with tubing and Dipro-fog oil (MFA-K).

### TECHNICAL DATA:

Max primary pressure: 16 bar  
Max capacity at 7 bar: 1200 l/min  
Hose connection: 7 mm  
Secondary pressure: 0,5 - 10 bar



MFA-K

Description	Item number
Dipro-fog	MFB
Lubricaton Oil (0,5 l)	MFA-K

## Accessories for Air-Driven Machines



HSL-M

Each air-driven machine requires a quick coupling (HSL-M) as well as a fog lubricating device type Dipro-fog MFB to ensure efficient lubrication at all times.

A 3-way hose connection and air hose is also available.

Description	Item number
Quick Coupling	HSL-M
3-way hose connection	MFA-T2
Air Hose	MFA-S

**DIPROFIL**<sup>®</sup>

**DIAMANTPRODUKTER AB**

**Since 1950**

Please contact us or your local dealer to obtain more information  
about other Diprofil products

Local dealer:

[www.diprofil.com](http://www.diprofil.com)

Diamantprodukter AB, Box 8093, SE-163 08 Spånga, Sweden  
Tel: +46 8 546 509 60 Fax: +46 8 546 509 61 e-mail: [sales@diprofil.se](mailto:sales@diprofil.se)